

HIGH-PERFORMANCE CHLORINATED RUBBER & ALKYD ZONE MARKING PAINT

Crafco's Action Pave Zone Marking Paints are formulated for excellent durability, UV resistance and colorfastness. We offer both chlorinated rubber and alkyd formulations in different colors to suit applications from airports and streets to crosswalks and parking lots. Our zone paints are sprayable and meet a variety of federal specifications.

CHLORINATED RUBBER

Crafco's Chlorinated rubber traffic paint provides high-performance, quick dry times, and excellent durability on a wide range of pavement types.

Excellent color retention makes chlorinated rubber zone marking paint ideal for problem areas that tend to "bleach out" in the sun. We offer a range of chlorinated rubber products for a variety of purposes.

Features:

- Available in white, yellow, red and black
- Dry Time: <15 Minutes
- Voc: <450 g/L
- Meets performance requirements for federal specs:
- AASHTO M-248 Type F
- AASHTO M-248 Type N
- GSA A-A- 2886B
- TT-P 115E Type III

ALKYD

Crafco's high-performance alkyd traffic paint has been a workhorse in the traffic paint industry for years. Formulated with the highest-quality raw materials, these alkyd traffic paints provide long-lasting durability and color retention on concrete and asphalt.

Features:

- · Available in yellow
- Dry Time: <15 Minutes
- Meets performance requirements for federal specs:
- AASHTO M-248 Type S
- GSA A-A-2886B
- TT-P-115 Type I
- TT-P-85E



6165 W. Detroit St., Chandler AZ 85226 602.276.0406 | www.crafco.com

CHLORINATED RUBBER & ALKYD ZONE MARKING PAINT

Action Pave®



CHLORINATED RUBBER

ALKYD

Application	Spray	Spray
Dry-No-Pick-Up	<15′	<15′
Substrates	Asphalt, Concrete	
Federal Spec	AASHTO M-248 Type F AASHTO M-248 Type N GSA A-A- 2886B T-P 115E Type III	AASHTO M-248 Type S GSA A-A-2886B TT-P-115 Type I TT-P-85E
Cleanup Method	Acetone	
BLACK	P667BLUCR	
WHITE	P627WHTCR	
YELLOW	P647YELCR	P64PYELA
RED	P657REDCR	
BIKE PATH GREEN	ON REQUEST, PLEASE SPEAK WITH YOUR	
VETERAN PURPLE	REPRESENTATIVE FOR MORE INFORMATION.	
Sizes	5GL	
VOC Level	<450 g/L	<450 g/L
	STANDARDS COMPLIANCE	
OTC: <150 g/L	No	
SCAQMD: <100 g/L	No	
CARB SCM2007: <100 g/L	No	
Canada VOC: <450 g/L	No	
LADCO: <150 g/L	No	

ZONE PAINT FOR LASTING RESULTS



