SAFETY DATA SHEET



1. Identification

Product identifier Crafco Mastic, Polypatch and Matrix Products

Other means of identification None.

Recommended use Pavement Patching and Repair

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer: Crafco, Inc.

Address: 6165 West Detroit St.

Chandler, AZ 85226 USA

Contact Name: Jim Chehovits **Telephone:** 602-276-0406

E-mail: jim.chehovits@crafco.com **CHEMTREC:** 800-424-9300 (North America)

+ 1-703-527-3887 (International)

Not available. **Supplier**

2. Hazard identification

Physical hazards Not classified. **Health hazards** Not classified. **Environmental hazards** Not classified.

*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

Label elements

Hazard symbol None.

Not applicable. Signal word **Hazard statement** Not applicable.

Precautionary statement

Prevention Not applicable. Response Not applicable. Storage Not applicable. **Disposal** Not applicable. Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC		64742-52-5	0 - 75
SILICA, CRYSTALLINE, QUARTZ		14808-60-7	0 - 75
ASPHALT		8052-42-4	10 - 40
CALCIUM CARBONATE		471-34-1	0 - 10
Other components below reportable	e levels		26.06

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist. Get medical attention, if needed.

Material name: Crafco Mastic, Polypatch and Matrix Products SDS CANADA 1/8 Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Thoroughly wash (or discard) clothing and shoes

before reuse.

Not available.

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO **Eye contact**

NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and

Ingestion Rinse mouth. Do not induce vomiting. Do not use mouth-to-mouth method if victim ingested the

substance. Call a POISON CENTER or doctor/physician if you feel unwell.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

In case of ingestion, the decision of whether or not to induce vomiting should be made by the attending physician. Certain pre-existing conditions may make workers particularly susceptible to the effects of this chemical: asthma, allergies, impaired pulmonary function.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Discard any shoes or clothing items that cannot be decontaminated.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Addition of water or foam to the fire may cause frothing.

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions Fire may produce irritating, corrosive and/or toxic gases.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection.

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. In the event of fire, cool tanks with water spray. By fire, toxic gases may be formed (COx, NOx). Keep run-off water out of sewers and

water sources. Dike for water control.

Specific methods In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with

Do not use a solid water stream as it may scatter and spread fire.

water spray. Use water spray to cool unopened containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ventilate closed spaces before entering them. Do not touch or walk through spilled

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Dike far ahead of spill for later disposal. Following product recovery, flush area with water.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Runoff or release to sewer, waterway or ground is forbidden.

7. Handling and storage

Precautions for safe handling

The product is non-combustible. If heated, irritating vapors may be formed. Do not use in areas without adequate ventilation. Wash hands thoroughly after handling. Wash hands after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep the container tightly closed and dry. Store in a closed container away from incompatible materials. Keep out of the reach of children.

Material name: Crafco Mastic, Polypatch and Matrix Products SDS CANADA 2/8

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Value			F
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
DISTILLATES PETROLEUM), HYDROTREATED HEAVY HAPHTHENIC (CAS H4742-52-5)	TWA	5 mg/m3	Inhalable fraction.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Canada. Alberta OELs (Occupatio Components	nal Health & Safety Code, S Type	chedule 1, Table 2) Value	Form
SPHALT (CAS 8052-42-4)	TWA	5 mg/m3	Fume.
ALCIUM CARBONATE (CAS 71-34-1)	TWA	10 mg/m3	
DISTILLATES PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Canada. British Columbia OELs. (Safety Regulation 296/97, as am Components		its for Chemical Substances, Value	Occupational Health Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Aerosol, inhalable.
CALCIUM CARBONATE (CAS 471-34-1)	STEL	20 mg/m3	Total dust.
	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
DISTILLATES PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	TWA	1 mg/m3	Mist.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Canada. Manitoba OELs (Reg. 21 Components	7/2006, The Workplace Saf Type	ety And Health Act) Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
		E ma/m2	Turk alakla fua atian
PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS	TWA	5 mg/m3	Inhalable fraction.
(PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 54742-52-5) SILICA, CRYSTALLINE,	TWA	0.025 mg/m3	Respirable fraction.
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) Canada. Ontario OELs. (Control o	TWA	0.025 mg/m3	

Material name: Crafco Mastic, Polypatch and Matrix Products 5013 Version #: 01 Issue date: 01-16-2019

Components	Туре	Value	Form	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.	
Canada. Quebec OELs. (Mic Components	nistry of Labor - Regulation respect Type	ing occupational health an Value	nd safety) Form	
ASPHALT (CAS 8052-42-4)	TWA	5 mg/m3	Fume.	
CALCIUM CARBONATE (CAS 471-34-1)	TWA	10 mg/m3	Total dust.	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	STEL	10 mg/m3	Mist.	
,	TWA	5 mg/m3	Mist.	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.	
Canada. Saskatchewan OE Components	Ls (Occupational Health and Safety Type	Regulations, 1996, Table Value	21) Form	
ASPHALT (CAS 8052-42-4)	15 minute	1.5 mg/m3	Inhalable fraction.	
	8 hour	0.5 mg/m3	Inhalable fraction.	
CALCIUM CARBONATE (CAS 471-34-1)	15 minute	20 mg/m3		
	8 hour	10 mg/m3		
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	15 minute	10 mg/m3		
	8 hour	5 mg/m3		
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	8 hour	0.05 mg/m3	Respirable fraction.	
logical limit values	No biological exposure limits noted for	the ingredient(s).		
propriate engineering trols	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.			
ividual protection measure Eye/face protection	s, such as personal protective equip Wear safety glasses; chemical goggles (if handling molten material).		ar chemical goggles; face sl	
Skin protection	·			
Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.			
Other	Wear suitable protective clothing and eye/face protection. Use of an impervious apron is recommended.			
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.			
Thermal hazards	During product use, there is a risk of thermal burns.			
neral hygiene	When using do not smoke. Avoid conta		vith skin. Keep away from fo	

9. Physical and chemical properties

Appearance Solid. Solid. **Physical state Form** Solid.

> Color Black, Dark brown

Odor Product is a black, semi-solid with a burnt tar odor.

Odor threshold Not available. pН Not available.

Melting point/freezing point 150 - 250 °F (65.56 - 121.11 °C) ASTM D36 Softening Point

Initial boiling point and

> 800 °F (> 426.67 °C)

boiling range

Flash point > 400.0 °F (> 204.4 °C)

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

4.07 hPa estimated Vapor pressure Not available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

> 700 °F (> 371.11 °C) **Auto-ignition temperature**

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Not Available **Density**

0 % **Percent volatile** 1 - 2.2 Specific gravity

10. Stability and reactivity

Reactivity

Chemical stability Material is stable under normal conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

Conditions to avoid Strong oxidizing agents.

Incompatible materials Incompatible with oxidizing agents.

Hazardous decomposition Upon decomposition, product emits acrid dense smoke with carbon dioxide, carbon monoxide, trace

products oxides of nitrogen and sulfur, and water.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Irritating to skin.

Eye contact Causes eye irritation. Molten material will produce thermal burns. **Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Not available.

Symptoms related to the

toxicological characteristics

physical, chemical and

Information on toxicological effects

Acute toxicity

Components Species Test Results

CALCIUM CARBONATE (CAS 471-34-1)

Acute Oral

LD50 Rat 6450 mg/kg

Skin corrosion/irritation Defats the skin. Causes irritation.

Serious eye damage/eye

irritation

Irritating to eyes.

Respiratory or skin sensitization

Respiratory sensitization Not available. **Skin sensitization** Irritating to skin.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. This product

contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the

normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

Reproductive toxicityContains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not available.

Specific target organ toxicity

- repeated exposure

Not available.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. May cause eczema-like skin disorders (dermatitis).

12. Ecological information

EcotoxicityThis product has no known eco-toxicological effects. Not expected to be harmful to aquatic

organisms.

Components Species Test Results

CALCIUM CARBONATE (CAS 471-34-1)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) > 56000 mg/l, 96 hours

Persistence and degradabilityNot available.Bioaccumulative potentialNot available.Mobility in soilNot available.Other adverse effectsNot available.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.

When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261.

Hazardous waste code Not applicable.

SDS CANADA

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

Waste from residues / unused products

Dispose of in accordance with local regulations.

Contaminated packaging Offer rinsed packaging material to local recycling facilities.

14. Transport information

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

General information Not regulated as dangerous goods.

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the CPR and the SDS

contains all the information required by the CPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

The product does not need to be labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No

Material name: Crafco Mastic, Polypatch and Matrix Products

SDS CANADA 5013 Version #: 01 Issue date: 01-16-2019

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 01-16-2019

Version # 01

Further information HMIS® is a registered trade and service mark of the NPCA.

References ACGIH

EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties

Transport Information: Material Transportation Information

Regulatory Information: Risk Phrases - Class.

GHS: Classification

Material name: Crafco Mastic, Polypatch and Matrix Products

5013 Version #: 01 Issue date: 01-16-2019

8 / 8