

Delivering Confidence Through Innovation, Quality and Value Since 1976

ACTION PAVE®
LEVELING PATCH

PART No. 11961LP

FEBRUARY 2022

6165 W Detroit St. • Chandler AZ 85226 +1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513 www.crafco.com

#### **READ BEFORE USING THIS PRODUCT**

## **GENERAL**

Action Pave Leveling Patch is a ready to use, self-adhering, heavily fortified homogeneous mixture of liquid asphalt, sand, mineral fillers, fibers and latex for extra strength and flexibility. Action Pave Leveling Patch is a long-term asphalt leveler and repair patching formula that has a cement-like consistency and dries black to match existing asphalt pavement. Action Pave Leveling Patch is a heavily bodied, thick formula that fills cracks better than the liquid fillers and has less shrink. VOC 0 g/L

## **RECOMMENDED USES**

Action Pave Leveling Patch is used for leveling low spots, uneven depressions, and ruts and for deteriorated surfaces and medium sized cracks. Fills cracks in asphalt parking lots, driveways, playgrounds, walkways, etc. Good for use on: Potholes, alligator cracks, depressions, overlays, curbs, utility cut-outs, streets and highways, driveways and parking lots, golf cart paths, ADA access ramps and more.

## **INSTALLATION**

- Application
  - o To apply **Action Pave Leveling Patch**, use trowel or spread by hand squeegee. For severely distressed areas, it is recommended to apply **Action Pave Tack Coat** to the patch area prior to installing **Action Pave Leveling Patch** for maximum adhesion and covering it with **Action Pave Pavement Sealer** once it has cured for enhanced durability. Initial set will typically occur within one hour in temperature range of 50 °F (10 °C) to 90 °F (32.2 °C). Allow product to become dry and firm to the touch at which time the repair area can be opened for use.
  - o For repairs for depths equal to or less than 1" (25.4 mm), it is recommended that the compound be applied in ¼" (6.4 mm) layers. Allow product to become dry and firm to the touch before adding the next layer. This will assure proper drying and strength. Before sealcoating, allow product to become dry and firm to the touch at which time the repair area can be opened for use. For repairs greater than 1" (25.4 mm), it is recommended to use **Crafco HP Cold Patch products.**
- Coverage
  - Depends on surface porosity and depth
- Surface Preparation
  - o Surface must be cleaned of dust, dirt, and debris.

### **LIMITATIONS**

- Do not apply when surface temperature is below 50 °F (10 °C) or when surface temperature is above 130 °F (55 °C).
- Do not apply when rain, fog or high humidity is imminent.

# **PACKAGING AND AVAILABILITY**

5 Gal. (18.9 L) pails.

#### **STORAGE**

- Close cover tightly
- Do not store in direct sunlight.
- Keep from freezing
- Storage temperature range 40 90 °F
- Dispose of in accordance with state and federal regulations

## **WARRANTY**

ACTION PAVE® Leveling Patch is warranted by the manufacturer to meet specification requirements at time of shipment. Techniques used for pavement preparation prior to Action Pave Leveling Patch application are beyond manufacturer control as are use and application of Action Pave Leveling Patch; therefore, the manufacturer shall not be responsible for improperly applied or misused Action Pave Leveling Patch. Remedies against the manufacturer are limited to replacing nonconforming product or refund (full or partial) of purchase price. All claims for breach of this warranty must be made within three (3) months of delivery date. There shall be no other warranties expressed or implied. For optimum performance, follow recommendations for Action Pave installation.

No informal dispute mechanism has been established. Notice must be given in writing to Crafco, Inc 6165 W. Detroit St., Chandler, AZ 85226. A sample of the product claimed defective must be retained together with satisfactory proof of purchase. No claim will be honored if the lot number(s) are not provided therewith. THIS WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES AND EXPRESSLY EXCLUDES ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR PARTICULAR PURPOSE, AS WELL AS LIABILITY FOR CONSEQUENTIAL DAMAGES. Crafco Sales or Technical Representatives have no authority to extend any guarantee beyond that outline above.