# **SAFETY DATA SHEET**



# 1. Identification

Product identifier HP Asphalt Cold Patch, SC-800 Cold Patch and Perma Repair

Other means of identification None.

**Recommended use** Pavement Patching and Repair

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

**Manufacturer:** Crafco, Inc.

**Address:** 6165 West Detroit St.

Chandler, AZ 85226 USA

**Contact Name:** Crafco Materials Engineering

**Telephone:** 602-276-0406 **E-mail:** sales@crafco.com

**CHEMTREC:** 800-424-9300 (North America)

+ 1-703-527-3887 (International)

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

OSHA defined hazards Not classified.

No hazards resulting from the material as supplied.

**Label elements** 

Hazard symbol None.

**Signal word** Not applicable. **Hazard statement** Not applicable.

**Precautionary statement** 

PreventionNot applicable.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.

Hazard(s) not otherwise

classified (HNOC)

None known.

**Supplemental information** None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Aggregate		Mixture	60 - 85
ASPHALT		8052-42-4	3 - 7
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT		64742-47-8	< 1
KEROSINE (PETROLEUM), HYDRODESULFURIZED		64742-81-0	< 1
Other components below reportable	e levels		0.15

# 4. First-aid measures

**Inhalation** If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve

or other proper respiratory medical device. Call a physician if symptoms develop or persist.

Wash off with soap and plenty of water. For minor skin contact, avoid spreading material on Skin contact

unaffected skin. Wash clothing separately before reuse. Get medical attention if irritation develops

and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO **Eye contact** 

NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention if

irritation develops and persists.

Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If **Ingestion** 

> vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If

ingestion of a large amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed

Not available.

**Indication of immediate** medical attention and special treatment needed

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation.

Symptoms may be delayed.

**General information** IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before re-use.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

**Special protective equipment** 

and precautions for firefighters

Fire fighting

equipment/instructions

Water. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use a solid water stream as it may scatter and spread fire.

Fire may produce irritating, corrosive and/or toxic gases.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective

clothing will only provide limited protection.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out, Water

runoff can cause environmental damage.

**Specific methods** In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with

water spray.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear appropriate protective equipment and clothing during clean-up. Ventilate closed spaces before entering them. Avoid inhalation of vapor, fumes, dust and/or mist from the spilled material.

Methods and materials for containment and cleaning up Collect spillage. Sweep up or vacuum up spillage and collect in suitable container for disposal. Avoid dust formation. Following product recovery, flush area with water. Do not allow material to contaminate ground water system.

**Environmental precautions** 

Avoid release to the environment. Refer to special instructions/safety data sheets. Do not contaminate water.

## 7. Handling and storage

Precautions for safe handling

Keep formation of airborne dusts to a minimum. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact with eyes. Use personal protective equipment as required. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash thoroughly after handling. Avoid release to the environment. Do not empty into drains. Use appropriate container to avoid environmental contamination. Do not heat above 120°F (48.8°C) when using.

Conditions for safe storage, including any incompatibilities

The pressure in sealed containers can increase under the influence of heat. Store in  $\epsilon$  well-ventilated place. Keep container tightly closed. Store in a closed container away from incompatible materials. Keep away from food, drink and animal feedingstuffs.

# 8. Exposure controls/personal protection

#### **Occupational exposure limits**

IIS	ACGTH	I Three	shold	I imit	<b>Values</b>
US.	ACGIL	ııııe	siiviu	LIIIIL	values

Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0)	TWA	200 mg/m3	Non-aerosol.

#### **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)	TWA	100 mg/m3	
KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0)	TWA	100 mg/m3	

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Exposure guidelines** Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should

be monitored and controlled.

#### **US ACGIH Threshold Limit Values: Skin designation**

KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS Can be absorbed through the skin.

64742-81-0)

**Appropriate engineering** 

Adequate ventilation should be provided so that exposure limits are not exceeded.

controls

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Safety glasses.

Skin protection

**Hand protection** Wear protective gloves.

**Other** Wear suitable gloves and eye/face protection.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

**Thermal hazards** Not available.

General hygiene considerations

When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Keep away from food and drink. Handle in

accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

Appearance Pellets.
Physical state Solid.
Form Solid.
Color Black.

Odor Hydrocarbon-like.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.

Initial boiling point and

boiling range

> 437 °F (> 225 °C)

Flash point > 200.0 °F (> 93.3 °C) Cleveland Open Cup

Material name: HP Asphalt Cold Patch, SC-800 Cold Patch and Perma Repair 5004 Version #: 04 Revision date: 05-29-2020 Issue date: 02-09-2016

**Evaporation rate** Not available. **Flammability (solid, gas)** Not available. **Upper/lower flammability or explosive limits** 

Flammability limit - lower

Not available.

(%)

Flammability limit -

upper (%)

Not available.

**Explosive limit - lower** 

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 905 °F (485 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Percent volatile < 2 % Specific gravity 2.00 - 2.50

## 10. Stability and reactivity

**Reactivity** Not available.

**Chemical stability** Stable under normal temperature conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

**Conditions to avoid** Heat, flames and sparks. Avoid high temperatures.

**Incompatible materials** Oxidizing materials.

Hazardous decomposition Irritants. Upon decomposition, product emits acrid dense smoke with carbon dioxide, carbon

**products** monoxide, trace oxides of nitrogen and sulfur, and water.

#### 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea

**Skin contact** Molten material will produce thermal burns.

**Eye contact** Molten material will produce thermal burns. Harmful in contact with eyes.

**Ingestion** May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

# Information on toxicological effects

Acute toxicity

Skin corrosion/irritation

Serious eye damage/eye

Not available.

Not available.

None known.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not available. **Skin sensitization** None known.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity** Not classified. **Specific target organ toxicity** Not available.

- single exposure

Draduct

Specific target organ toxicity

- repeated exposure

Not available.

**Aspiration hazard** Not available.

**Chronic effects** Hazardous by OSHA criteria. Prolonged inhalation may be harmful. Repeated absorption may cause

disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause

Toot Dooulte

chronic effects. Not expected to be hazardous by WHMIS criteria.

**Further information** Symptoms may be delayed. This product has no known adverse effect on human health

Chacias

# 12. Ecological information

**Ecotoxicity** This product has no known eco-toxicological effects.

Product		Species	lest Results
HP Asphalt Cold Patch	, SC-800 Cold Patc	h and Perma Repair	
Aquatic			
Crustacea	EC50	Daphnia	13475.833 mg/l, 48 hours estimated
Fish	LC50	Fish	423.1804 mg/l, 96 hours estimated
Components		Species	Test Results
DISTILLATES (PETRO	LEUM), HYDROTRE	ATED LIGHT (CAS 64742-47-8)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Mobility in soil Not available.

Other adverse effects Not available.

#### 13. Disposal considerations

**Disposal instructions** Dispose of contents/container in accordance with local/regional/national/international regulations.

When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261.

Waste from residues /

unused products

Dispose of in accordance with local regulations.

**Contaminated packaging** No special precautions.

# 14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

## 15. Regulatory information

**US federal regulations**This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

## **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### **SARA 302 Extremely hazardous substance**

Not listed.

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

## **California Proposition 65**

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8) KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 02-09-2016 **Revision date** 05-29-2020

Version # 04

NFPA ratings Health: 1

Flammability: 0 Instability: 0

**References** ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information** Physical & Chemical Properties: Multiple Properties

Regulatory Information: United States